

| 型号 Model | 输出电压 (V) Output voltage(V) | 输出电流 (A) Output current (A) | 输出功率 (W) Power (W) | 效率 (%) Eff (%) | 功率因数 (%) PF (%) | 尺寸 (L*W*H)mm Dimensions(L*W*H)mm |
|-------------|-------------------------------|--------------------------------|-----------------------|-------------------|--------------------|-------------------------------------|
| X2-75-56 | 30-56 | 0.6-1.6 | 75 | 92.5 | 0.96 | 105*66*30.5 |
| X2-75-150 | 70-150 | 0.5-1.05 | 75 | 92.5 | 0.96 | 105*66*30.5 |
| X2-100-56 | 30-56 | 1.0-2.4 | 100 | 92.5 | 0.97 | 165*66*34 |
| X2-100-150 | 70-150 | 0.5-1.05 | 100 | 92.5 | 0.97 | 165*66*34 |
| X2-120-56 | 30-56 | 1.0-2.4 | 120 | 92.5 | 0.97 | 177*66*34 |
| X2-120-150 | 70-150 | 0.5-1.05 | 120 | 92.5 | 0.97 | 177*66*34 |
| X2-150-56 | 30-56 | 1.5-3.2 | 150 | 92.5 | 0.97 | 177*66*34 |
| X2-150-150 | 70-150 | 1-2.15 | 150 | 92.5 | 0.97 | 177*66*34 |
| X2-200-56 | 30-56 | 2.5-4.2 | 200 | 93 | 0.97 | 197*70*39 |
| X2-200-150 | 70-150 | 1.0-2.1 | 200 | 94 | 0.97 | 197*70*39 |
| X2-240-56 | 30-56 | 3.0-5.6 | 240 | 93 | 0.97 | 221*70*39 |
| X2-240-150 | 70-150 | 1.0-3.0 | 240 | 94 | 0.97 | 221*70*39 |
| X2-320-56 | 30-56 | 3.0-8.4 | 320 | 93.5 | 0.97 | 238*75*43.5 |
| X2-400-56 | 30-56 | 3.0-9.5 | 400 | 93 | 0.97 | 238*75*43.5 |
| X2-720-56 | 150-300 | 0.7-2.8 | 720 | 94.5 | 0.97 | 280*144*49.5 |